










模塊尺寸和輸入/輸出電壓可根據客戶的機制進行定制。

Watts	Type	Picture	Material NO	IC	Overall			Coil	Performance			
					L (mm)	W (mm)	H (mm)	Size	Input Voltage	output Voltage	Amh	Efficiency
20W	RX		TMRX20V11-037	B3	130	55	3.5	外徑:50x50mm	5V	5V	Max 4A	80%
20W	RX		TMRX20V40-033	B3	120	52	5	外徑:38x 41mm 內徑:22*12mm	5V	5V	Max 4A	80%
20W	RX		TMRX20V11-007	B3	130	55	5	外徑: 40mm 內徑: 15mm	5V	5V	Max 4A	80%
40W	RX		TMRX40V54-031	B3	70	70	14.2	52x52x5.9mm	5V,12V, 19V,24V	5V,12V, 19V,24V	Max 8A	80%
100W	TX		TMTX100V21-031(a4)	A4	130	70	24.3	52x52x5.9mm	5V,12V, 19V,24V	5V,12V, 19V,24V	Max 20A	85%
100W	TX		TMTX100V21-031(a5)	a5	130	70	31.9	52x52x5.9mm	5V,12V, 19V,24V	5V,12V, 19V,24V	Max 20A	85%
100W	RX		TMRX100V11-031	b3	70	70	8.5	52x52x5.9mm	5V,12V, 19V,24V	5V,12V, 19V,24V	Max 20A	85%